

5M IP IR Fisheye Dome



NVF2-45-R

Features

- 5MP 360-degree camera
- 1/1.8" high sensitivity sensor
- Maximum resolution 2952 (horizontal) X 1944 (vertical) / 30fps
- Horizontal angle of view 180 degrees / 180-degree fisheye lens
- Day & Night (ICR) / IR reach distance 17 meters
- Backlight compensation (WDR) / 3DNR
- SD/SDHC/SDXC memory slot
- PoE IEEE 802.3af/Class3
- IP66/IK09



Dimension (mm)



Specification

Video	
Image Sensor	1/1.8" 6.4M CMOS
Channels	1
Total Pixel	3096(H) X 2080(V)
Max Resolution	2592(H) X 1944(V)
MIN. Illumination	0.39Lux 0Lux with IR (F2.5)
Only installer Video Output	No
S/N(signal/noise) Ratio	50dB
Scanning Mode	Progressive Scan

Lens	
Focal Length	1.55mm
Aperture	F2.5
Lens Type	Fixed
IRIS Type	Auto Exposure
Horizontal Angle	D:185 , H:185 , V:185
Pan / Tilt / Zoom	Zoom :Fixed

Operational	
Shutter Speed	Auto / Manual (1/15 ~ 1/32000) Anti-Flicker Slow Shutter(1/2,1/3,1/5,1/6,1/7.5, 1/10)
Auto Gain Control (AGC)	Auto
Day & Night	TDN (True Day & Night)
Digital Noise Reduction	3D DNR
Wide Dynamic Range (WDR)	No
Dynamic Range	120dB or above
LEDs	H3IR
LED Distance	55ft(17m)
Privacy Zone	Yes
Function	Motion-Detection Mirror&Flip

Intelligent Video Analytic	
AI Intelligent Video Analytic	No

Encoder (video & audio)	
Video Compression	H.264 H.265 MJPEG

Encoder (video & audio)

Support Resolution	H.265 : 2592x1944/2048x1536/1600x1200/640x480/640x360/384x288/352x240/320x240 H.264 : 2592x1944/2048x1536/1600x1200/640x480/640x360/384x288/352x240/320x240 MJPEG : 1600x1200/1280x1024/1280x960/1152x864/1024x768/800x600/640x480/480x360/384x288/320x240
Intelligent Codec	Yes
Multiple Profile Streaming Performance	Triple Streaming(3rd Only MJPEG)
Video BitRate	100Kbps~10Mbps
Bitrate Control	Multi Streaming CBR/VBR at H.265 (Controllable frame rate and Bandwidth)
Video Bitrate extra comment	Multi-rate for Preview and Recording
Audio Compression	G.711 ulaw
Special Feature	Dynamic ROI(Region of Interest)

I/O & Event

Audio In / Out	1 Line[1.0Vms, 3K ohm]/1 Line
Alarm In / Out	1 Line/1 Line
Mic	No
Event Trigger	Motion Alarm Network Disconnection Temperature Critical Illegal Login Schedule Sensor Detection
Event Notification	FTP E-Mail Alarm Out SD Card

Network

Ethernet	RJ45 (10/100Base-T)
Protocol	TCP/IP UDP AutoIP RTP(UDP/TCP) RTSP NTP HTTP HTTPS SSL DNS DDNS DHCP FTP SMTP ICMP SNMPv1/v2/v3(MIB-2) ONVIF
Security	HTTPS(SSL) IP filtering 802.1x Digest Authentication
Application Programming I/F	CGI API ONVIF
Web viewer	MS Edge® Google Chrome®
Video management software (VMS)	DW Spectrum® IPVMS
Support languages	English Korean Japanese
Edge storage	Micro SD
SD Card Socket	1

Electrical

Power Requirement	Adaptor is not included DC12V PoE IEEE 802.3af Class3
Power consumption	DC Max: 7.5W PoE Max: 8.7W


Environmental

Operating Temperature	-20°C ~ 50°C
Cold Start	No

Environmental	
Operating Humidity	10-90% RH(Non-Condensing)
Vandal Proof Casing	IK09
IP Rating	IP66
Other Certification	FCC CE ROHS

Mechanical	
Housing Model	VF2
Housing	Outdoor Dome Fisheye
Material	Aluminum-Die Casting
Color	White
Dimensions (W x D x H)	125mm 48mm
Weight	0.5kg

Compatible Accessories

 BC10 NPT	 BJC08 Angle Bracket	 GP02 Gang Bracket	 BJC03 Junction Bracket
 BW10 Wall Bracket	 BC10 Ceiling Bracket	 BJC09 Wall Junction Bracket	 BP01 Pole Mount Bracket



BCO01

Corner Mount Bracket